



NP-165 Trailer Specification Sheet

The following specifications are the **minimum requirements** for any over the road trailer to be used in conjunction with the NP-165 Newsprint Loading System designed by SP Industries, Inc., Hopkins, Michigan.

- Length:** Overall Trailer Length not to exceed 53'-0"
- Width:**
- | | |
|-------------------|-------------------------|
| <i>Overall</i> | 102-1/4" |
| <i>Inside</i> | 101" between side post. |
| Rear Door Opening | 98-1/4" |
- Height:** 96" Minimum and 110-1/4" Maximum Box Height
Floor Height Range of 48" to 53" from Ground.
- Floor:** Minimum of 1-3/8" finished thickness laminated hardwood, undercoated. Three 5/16 screws per board per bearer. Twelve gauge steel threshold angle. Supports spaced maximum of 9" apart and fastened securely to the frame of the trailer. Floor surface is to be smooth and free of holes, depressions, and gaps.
- Sides:** Minimum of .045 side post spaced on 16" centers for the 53' length. Sheet lap sealed. Sheet rivets on 2" centers at lap and 4" centers elsewhere.
- Lining:** Minimum of 1/4" exterior grade plywood, full height, over posts on side and nose. Sides are to be smooth and free of holes, depressions, and gaps.
- Bumper:** Fabricated of Structural channel and meeting DOT requirements. Bumper to have "V" bracing for automatic trailer/dock lock system.



Distributed By:



We are Social!



SP INDUSTRIES, INC.
2982 Jefferson Road
Hopkins, MI 49328

Phone: 800.592.5959 or 269.793.3232
Fax: 269.793.3232
Web: www.sp-industries.com
Email: sp_industries_inc@sp-industries.com